



THIS SPECIFICATION HAS BEEN PREPARED ON THE BASIS THAT 'CELUKA' LENDS NO CONTRIBUTION TO STRUCTURAL WALL BRACING OR UPLIFT, BEING SUBJECT ONLY TO EXTERNAL PRESSURE AND SUCTION LOADING.

'CELUKA CLADDING'  
 STANDARD LENGTH - 6M.  
 NOMINAL WEIGHT - 4.19/M<sup>2</sup>  
 COVER WIDTH - 250MM. AND 200MM  
 COLOUR - WHITE, BEIGE. RIGID P.V.C.  
 NOMINAL THICKNESS - 8MM.  
 OVERALL THICKNESS WHEN INSTALLED - 16MM.

FRAME:  
 MAXIMUM STUD SPACING - 450 MM.  
 FIXING: (FOR TERRAIN CATEGORIES 3, 2½ AND 2 AS DEFINED BY A.S. 1170 PART II)  
 NAILS: 40 MM SERRATED PLASTERBOARD NAILS.  
 1 NAIL PER PLANK PER STUD, PLACED ALONG THE NAILING GROOVE TO TIMBER STUD WORK OR, 1-20mm TYPE 17 N°8 BUGLE HEAD PHILIPS RECESSED SCREW TO LIGHT STEEL FRAMING.  
 STRUCTURAL MEMBRANE: PROVIDE STRUCTURAL PLYWOOD MEMBRANE TO EXTERNAL FACE OF STUDWORK FIXED IN ACCORDANCE WITH RELEVANT DEEMED TO COMPLY STANDARDS.  
 LINING: PROVIDE INTERNAL LINING AS NECESSARY.

FOR FURTHER INFORMATION, REFER NULINE "CELUKA BUILDING BOARDS" TECHNICAL SPECIFICATIONS.

MANUFACTURED BY  
 DURAFORM BUILDING PROFILES  
 29 POWERS ROAD,  
 SEVEN HILLS NSW 2147  
 FOR NULINE PROFILES PTY LTD  
 PHONE NUMBER: (049) 52 - 8088

CERTIFIED BY: *AA Bruch*  
 DATE: 30<sup>TH</sup> AUGUST 1990.

<b>CELUKA CLADDING.- FIXING DETAILS</b>	
<b>DESIGN DATA SHEET.</b>	
NORTHERN TERRITORY CYCLONIC AREAS 3, 2½ & 2.	DRG. N° <b>M208/1</b>
APPROVED BY: <i>[Signature]</i>	DATE: <b>29/10/90</b>