

MASONRY ANCHORS TO BE LOCATED 100 MIN. FROM EDGE OF MASONRY.

MINIMUM STEEL SECTION SIZE 125x75x6 ANGLE

GUSSET 100x85x3 THICK GALVABOND STEEL PLATE SPACED AT 870 MAX CTS. SEE DRAWING N° 3

WINDLOCK CLIP FIXED TO CURTAIN WITH FOUR $\phi 3$ mm N° 73 MS 4-6 POP RIVETS, TWO FROM FRONT AND TWO FROM REAR FITTED ON EVERY SECOND FLUTE OF CURTAIN.

FIX ANGLE TO REINFORCED MASONRY WITH M12 M.A. @ SAME CTS. AS GUSSET PLATES

GUIDE METAL STRIP

POLYGLIDE

CURTAIN

STEEL FIX

200 REINFORCED MASONRY FIX

100 EDGE DISTANCE FOR MASONRY ANCHORS - FABRICATE LUG TO SUIT.

$\phi 12$ MASONRY ANCHORS INTO CORE FILLED AND REINFORCED MASONRY

WARNING
Product Approval Withdrawn
March 2013

GLIDEROL ROL-A-DOORS Pty Ltd.
Holden Hill
Adelaide S.A.

**GLIDEROL GARAGE DOOR
B SERIES INDUSTRIAL ROLLER
DOORS WITH WINDLOCKS**

**IRWIN, JOHNSTON & PARTNERS
(A.T.) ENGINEERS PTY LTD
CONSULTING ENGINEERS**
82 SMITH STREET, DARWIN, 5780
TEL (089318071) FAX (089314010)

CERTIFIED
[Signature]
DATE Jan '94
JOB No. 5047

DESIGN DATA SHEET

DARWIN CYCLONE AREA

SHEET No. A

DRAWN T.McK

APPROVED *[Signature]*

DATE 2-3-94

M407/1